

SHAWANO COUNTY PRIVY PERMIT

Date: _____ Fee: \$ 175.00 Permit Number: _____

Property Owner's Name: _____

Mailing Address: _____

City: _____ State: _____ Zip Code: _____

Tax Parcel #: _____

Town, City, Village: _____ 911 Address: _____

Property Location: _____ 1/4 _____ 1/4, Sec. _____, T _____ N, R _____ E

Subdivision or Plat: _____, Lot # _____, Block # _____

Zoning District: _____ **Note: Privies are prohibited in all residential zoning districts**

Type of Privy: _____ Pit* _____ Vault

***A copy of a soil boring description completed by a certified soil tester (CST) verifying depth of suitable soil is required**

Bldg. Size: _____ ft. wide x _____ ft. long Height: _____ ft.

Type of Construction: _____

- Privy shall maintain the following minimum horizontal setback distances:
 - 50 feet from any well and all water bodies (NR 812.08 Table A)
 - 25 feet from all doors and windows of any building (POWTS Sec. 12.1)
 - 25 feet from the right-of-way of any street or other public thoroughfare (POWTS Sec. 12.1)
 - 25 feet from all property lines (POWTS Sec. 12.1)
- A privy may be permitted only when the building served by the privy is not provided with plumbing or water service.
- Privies for public use shall meet the requirements of s. DSPS 391.12 and DSPS 362.2900.
- No plumbing shall be installed in the privy.
- Privy (public use) shall be provided with suitable approach, such as concrete, gravel or cinder walk (DSPS 362.2900 (3) c (1) and POWTS Sec. 12.2 (2)).
- Privy (public use) foundations shall be of concrete or other masonry (POWTS Sec. 12.2 (3)).
- Privies shall be constructed in such a manner so as to exclude flies, rats and other vermin. Doors should be self-closing and vents shall be a min. 3" diameter (DSPS 391.12 (2) b (1), terminate at least 8" above the roof (DSPS 382.31 (16)a and be provided with an effective screening to prevent entry by insects (DSPS 391.12 (2) b (3) and ventilating hood.
- A vault type privy with a minimum capacity of 200 gals. (DSPS 391.12 (1)a) and shall conform with the requirements of s. SPS384.25 relating to holding tanks
- The privy shall be kept clean and sanitary (POWTS Sec. 12.1)
- Servicing and maintenance openings for vaults shall be at least 23" wide and extend at least 4" above finished grade (DSPS 384.25 (7)e).
- The contents of the pit or vault shall be pumped by a licensed pumper only and disposed of in accordance with NR 113 Wisconsin Administrative Code.
- Privy shall comply with all applicable standards of Wisconsin Adm. Code SPS 391.12
- **OWNER SHALL CONTACT THE SHAWANO COUNTY ZONING OFFICE, WHEN THE PRIVY IS CONSTRUCTED, FOR AN ON-SITE INSPECTION (Phone # 715-526-6766)**

OWNER'S SIGNATURE: _____ DATE: _____

ISSUING AGENT SIGNATURE: _____ DATE: _____

INSPECTION AGENT SIGNATURE: _____ DATE: _____

AP 1/03; Rev. SF 10/07 & 1/08; Rev. RF 4/2015; KE 12/24